



| FLUID SPECIFICATIONS (US & Canada) |             |   |                                     |                                     |                                     | 2006 - 2009 MY   |  Lexus |                                     |                                  |   |
|------------------------------------|-------------|---|-------------------------------------|-------------------------------------|-------------------------------------|--|---|-------------------------------------|----------------------------------|---|
| Vehicle Model                      | Engine Type | Engine Oil (Drain & Refill w/Filter Change) |                                     |                                     |                                     | Coolant<br><i>Toyota Super Long Life Coolant (SLLC)</i>                  | Manual Transmission   | Automatic Transmission              | Transfer Case                    | Front and Rear Differential   |
|                                    |             | 2006  | 2007                                | 2008                                | 2009                                |  | Drain & Refill  |                                     |                                  |   |
| ES330                              | 3MZ-FE      | 5W-30<br>5.0qt.                             |                                     |                                     |                                     | 2006: 9.7qt. SLLC  |   | ATF T-IV<br>U151E: 3.7qt.           |                                  |   |
| ES350                              | 2GR-FE      |   | 5W-30<br>6.4qt.                     | 5W-30<br>6.4qt.                     | 5W-30<br>6.4qt.                     | 2007-2009: 9.5qt. SLLC   |   | ATF WS*: U660E                      |                                  |   |
| GS300                              | 3GR-FSE     | 5W-30<br>2WD: 6.7qt.<br>4WD: 6.8qt.         |                                     |                                     |                                     | 2006: 9.6qt. SLLC  |   | ATF WS*<br>2WD: A960E<br>4WD: A760H | ATF WS*: UF1AE                   | API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or<br>80W-90 <sup>4</sup><br>Front-4WD: 0.73qt.<br>Rear- 2WD: 1.21qt.<br>Rear-4WD: 1.10qt.                      |
| GS350                              | 2GR-FSE     |   | 5W-30<br>2WD: 6.6qt.<br>4WD: 6.7qt. | 5W-30<br>2WD: 6.6qt.<br>4WD: 6.7qt. | 5W-30<br>2WD: 6.6qt.<br>4WD: 6.7qt. | 2007-2009: 9.6qt. SLLC   |   | ATF WS*<br>2WD: A960E<br>4WD: A760H | ATF WS*: UF1AE                   | API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or<br>80W-90 <sup>4</sup><br>Front-4WD: 0.73qt.<br>LT 75W-85 GL-5<br>2WD Rear: 1.42qt.<br>4WD Rear: 1.42qt.     |
| GS430                              | 3UZ-FE      | 5W-30<br>5.5qt.                             | 5W-30<br>5.5qt.                     |                                     |                                     | 2006-2007: 10.7qt. SLLC  |   | ATF WS*: A761E                      |                                  | Synthetic API GL-5<br>75W-90<br>1.42qt.   |
| GS450h                             | 2GR-FSE     |   | 5W-30<br>6.7qt.                     | 5W-30<br>6.7qt.                     | 5W-30<br>6.7qt.                     | 2007-2009:<br>Gas Engine: 9.8qt. SLLC<br>Power Control Unit: 3.1qt. SLLC |   | ATF WS*: L110                       |                                  | LT 75W-85 GL-5,<br>Synthetic API GL-5 75W-90<br>1.42qt.   |
| GS460                              | 1UR-FSE     |   |                                     | 0W-20<br>5W-20<br>9.1qt.            | 0W-20<br>5W-20<br>9.1qt.            | 2008-2009: 11.7qt. SLLC  |   | ATF WS*: AA80E                      |                                  | LT 75W-85 GL-5<br>1.42qt.   |
| GX470                              | 2UZ-FE      | 5W-30<br>6.5qt.                             | 5W-30<br>6.5qt.                     | 5W-30<br>6.5qt.                     | 5W-30<br>6.5qt.                     | 2006-2009: 13.6qt. SLLC  |   | ATF WS*: A750F                      | API GL-5 75W-90<br>VF4BM: 1.5qt. | LX 75W-85 GL-5 w/LSD:<br>LT 75W-85 GL-5 w/o LSD<br><br>Front: 1.48qt.<br>Rear: 3.2qt.   |
| IS250                              | 4GR-FSE     | 5W-30<br>2WD: 6.7qt.<br>AWD: 6.8qt.         | 5W-30<br>2WD: 6.7qt.<br>AWD: 6.8qt. | 5W-30<br>2WD: 6.7qt.<br>AWD: 6.8qt. | 5W-30<br>2WD: 6.7qt.<br>AWD: 6.8qt. | 2006-2009: 9.6qt. SLLC   | API GL-5<br>75W-90<br>RA62: 1.9qt.  | ATF WS*<br>2WD: A960E<br>AWD: A760H | ATF WS*: UF1AE                   | LT 75W-85 GL-5<br>2WD Rear: 1.22qt.<br><br>API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or<br>80W-90 <sup>4</sup><br>AWD Front: 0.74qt.<br>AWD Rear: 1.10qt. |
| IS350                              | 2GR-FSE     | 5W-30<br>6.7qt.                             | 5W-30<br>6.7qt.                     | 5W-30<br>6.7qt.                     | 5W-30<br>6.7qt.                     | 2006-2009: 9.6qt. SLLC   |   | ATF WS*: A760E                      |                                  | LT 75W-85 GL-5<br>Rear: 1.42qt.   |
| ISF                                | 2UR-GSE     |   |                                     | 5W-30<br>9.8qt.                     | 5W-30<br>9.8qt.                     | 2008-2009: 12.6qt. SLLC  |   | ATF WS*: AA80E                      |                                  | LT 75W-85 GL-5<br>Rear: 1.45qt.   |
| LS430                              | 3UZ-FE      | 5W-30<br>5.5qt.                             |                                     |                                     |                                     | 2006: 10.0qt. SLLC   |   | ATF WS*: A761E                      |                                  | Synthetic API GL-5 SAE 75W-90<br>Rear: 1.43qt.  |

<sup>1</sup> Above 40°F<sup>2</sup> Below 40°F<sup>3</sup> Above 0°F<sup>4</sup> Below 0°F

\* ATF WS fluid is not a standard drain and fill. To ensure proper fluid level, refer to the ATF adjustment procedure in the RM

| FLUID SPECIFICATIONS (US & Canada) |             |   |                          |                          |  | 2006 - 2009 MY   |                     |  Lexus     |  |  |
|------------------------------------|-------------|---|--------------------------|--------------------------|--|--|---------------------|---|--|--|
| Vehicle Model                      | Engine Type | Engine Oil (Drain & Refill w/Filter Change) |                          |                          |  | Coolant<br><i>Toyota Super Long Life Coolant (SLLC)</i>                    | Manual Transmission | Automatic Transmission  | Transfer Case  | Front and Rear Differential  |
|                                    |             | 2006  | 2007                     | 2008                     | 2009   |  |                     |   |  |  |
| LS460                              | 1UR-FSE     |   | 0W-20<br>5W-20<br>9.1qt. | 0W-20<br>5W-20<br>9.1qt. | 0W-20<br>5W-20<br>2WD: 9.1qt.<br>AWD: 9.5qt. | 2007-2009: 11.7qt. SLLC  |                     | ATF WS*<br>2WD: AA80E<br>AWD: AA80F   | LX 75W-85 GL-5<br>LF1A: 0.7qt.   | API GL-5 75W-85<br>AWD Front: 0.79qt.<br>Rear: 1.42qt.   |
| LS600h                             | 2UR-FSE     |   |                          | 0W-20<br>5W-20<br>9.5qt. | 0W-20<br>5W-20<br>9.5qt.                     | 2008-2009<br>Gas Engine: 11.7qt. SLLC<br>Power Control Unit: 2.5qt. SLLC   |                     | ATF WS*: L110F  | LX 75W-85 GL-5<br>LF1A: 0.74qt.  | LT 75W-85 GL-5<br>Front: 0.79qt.<br><br>LX 75W-85 GL-5<br>Rear: 1.42qt.                                      |
| LX470                              | 2UZ-FE      | 5W-30<br>7.2qt.                             | 5W-30<br>7.2qt.          |                          |  | 2006-2007:<br>w/rear heater: 16.3qt. SLLC<br>w/o rear heater: 15.6qt. SLLC |                     | ATF WS*: A750F  | API GL-4 or GL-5<br>75W-90<br>HF2A: 1.4qt.   | API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or<br>80W-90 <sup>4</sup><br>Front: 1.7qt.<br>Rear: 3.5qt. |
| LX570                              | 3UR-FE      |   |                          | 0W-20<br>5W-20<br>7.4qt. | 0W-20<br>5W-20<br>7.4qt.                     | 2008: 17.6qt. SLLC   |                     | ATF WS*: AB60F  | API GL-5<br>75W-90<br>JF2A: 1.53qt.  | LT 75W-85 GL-5<br>Front: 2.01qt.<br>Rear: 4.44qt.  |
| RX330                              | 3MZ-FE      | 5W-30<br>5.0qt.                             |                          |                          |  | 2006: 10.3qt. SLLC   |                     | ATF T-IV<br>2WD: U151E: 3.7qt.<br>4WD: U151F: 3.8qt.  | API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or<br>80W-90 <sup>4</sup><br>MF2A: 0.95qt. | API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or<br>80W-90 <sup>4</sup><br>Rear: 0.95qt.                 |
| RX350                              | 2GR-FE      |   | 5W-30<br>6.4qt.          | 5W-30<br>6.4qt.          | 5W-30<br>6.4qt.                              | 2007-2009: 8.9qt. SLLC   |                     | ATF WS*<br>2WD: U151E<br>4WD: U151F   |  | API GL-5 SAE 90 <sup>3</sup> ;<br>API GL-5 SAE 80 or 80W-90 <sup>4</sup><br>Rear: .95qt.                     |
| RX400h                             | 3MZ-FE      | 5W-30<br>5.0qt.                             | 5W-30<br>5.0qt.          | 0W-20<br>5W-20<br>5.0qt. |  | 2006-2008:<br>Engine: 10.9qt. SLLC<br>Inverter: 3.6qt. SLLC                |                     | ATF WS<br>Front: P310<br>w/oil cooler: 4.4qt.<br>w/o oil cooler: 4.2qt.<br>Rear: Q211: 1.9qt. |  |  |
| SC430                              | 3UZ-FE      | 5W-30<br>5.5qt.                             | 5W-30<br>5.5qt.          | 5W-30<br>5.5qt.          | 5W-30<br>5.5qt.                              | 2006-2009: 10.46qt. SLLC   |                     | ATF WS*: A761E  |  | Synthetic API GL-5 75W-90<br>1.42qt.   |

<sup>1</sup> Above 40°F<sup>2</sup> Below 40°F<sup>3</sup> Above 0°F<sup>4</sup> Below 0°F

\* ATF WS fluid is not a standard drain and fill. To ensure proper fluid level, refer to the ATF adjustment procedure in the RM